












<p><i>Complete Transmitter Specifications are located in the Transmitter Section.</i></p> <p><i>Complete Connection Head Specifications are located in the Accessories Section.</i></p>			Temperature Transmitters				
			T-440	T-441	T-442	T-642	T-642 w/Display
							
			Input: Pt100 RTD Only	Input: Thermocouple, RTD, Other	Input: Thermocouple, RTD, Other	Input: Thermocouple, RTD, Other	Input: Thermocouple, RTD, Other
Connection Heads			Programmable Head-Mounted Transmitter, (4 to 20) mA analog output	Programmable Head-Mounted Transmitter, Isolated, (4 to 20) mA analog output	Programmable Head-Mounted Transmitter, Isolated, HART®, protocol, (4 to 20) mA analog output	Programmable Field Transmitter, Dual Input, Isolated, HART®, protocol, (4 to 20) mA analog output	Programmable Field Transmitter, Dual Input, Isolated, HART®, protocol, (4 to 20) mA analog output with Digital display
31		Aluminum Screw-Cover Head	X	X	X		
34		Cast Iron Screw-Cover Head	X	X	X		
35		Aluminum Field Transmitter Housing				X	X
49		Flip-Top Aluminum Head	X	X	X		
63		White Polypropylene Screw-Cover Head	X	X	X		
91		316L Stainless Steel Screw- Cover Head	X	X	X		

Hart® is a registered trademark of Hart Scientific Foundation.