


Select desired leadwire type by order code number, followed by desired length in inches



ORDER CODES

Example Order Number:

K48GM - 012 - 01A,306 - 15 -

F1048

Page
MgO-5

4

	CODE	DESCRIPTION	AVAILABLE CALIBRATIONS					TEMP RATING
			J	K	T	E	N	
Fiberglass	F1	Fiberglass insulation - solid conductor	J	K	T	E	N	482 °C [900 °F]
	F1A	Fiberglass insulation - solid conductor - flexible armor	J	K	T	E	N	482 °C [900 °F]
	F1B	Fiberglass insulation - solid conductor - stainless steel overbraid	J	K	T			482 °C [900 °F]
	F3	Fiberglass insulation - stranded conductor	J	K	T			482 °C [900 °F]
	F3A	Fiberglass insulation - stranded conductor - flexible armor	J	K	T			482 °C [900 °F]
	F3B	Fiberglass insulation - stranded conductor - stainless steel overbraid	J	K	T			482 °C [900 °F]
	H1	Hi-temp fiberglass insulation - solid conductor	J	K				704 °C [1300 °F]
	H1A	Hi-temp fiberglass insulation - solid conductor - flexible armor	J	K				704 °C [1300 °F]
	H1B	Hi-temp fiberglass insulation - solid conductor - stainless steel overbraid	J	K				704 °C [1300 °F]
Teflon®	T3J	Individual stranded Teflon® leads - 12 inch limit	J	K				204 °C [400 °F]
	T1	Teflon® insulation - solid conductor	J	K	T	E		204 °C [400 °F]
	T1A	Teflon® insulation - solid conductor - flexible armor	J	K	T	E		204 °C [400 °F]
	T1B	Teflon® insulation - solid conductor - stainless steel overbraid	J	K				204 °C [400 °F]
	T1M	Teflon® insulation - solid conductor - mylar shield	J	K				204 °C [400 °F]
	T3	Teflon® insulation - stranded conductor	J	K	T			204 °C [400 °F]
	T3A	Teflon® insulation - stranded conductor - flexible armor	J	K	T			204 °C [400 °F]
PVC	P5	PVC insulation - solid conductor	J	K	T	E	N	105 °C [221 °F]
	P7	PVC insulation - stranded conductor	J	K	T			105 °C [221 °F]
	P5M	PVC insulation - solid conductor - aluminum/mylar shield	J	K	T			105 °C [221 °F]
	P7M	PVC insulation - stranded conductor - mylar shield	J	K				105 °C [221 °F]
	C3060	PVC insulated coil cord - stranded; 60" extended	J	K	T	E		105 °C [221 °F]
	C3120	PVC insulated coil cord - stranded; 120" extended	J	K	T			105 °C [221 °F]
Kapton®	K1	Kapton® insulation - solid conductor	J	K				316 °C [600 °F]
	K1A	Kapton® insulation - solid conductor - flexible armor	J	K				316 °C [600 °F]
	K3	Kapton® insulation - stranded conductor	J	K				316 °C [600 °F]
	K3A	Kapton® insulation - stranded conductor - flexible armor	J	K				316 °C [600 °F]

Insert wire code number and 3 digit "B" length code. **Example: F1036 = 36" B length.**

For assemblies requiring leadwire beyond the flexible armor, illustrated as "C" in drawing, insert 3 digit "C" length after armor length. **Example: T1A036-012 = 36" B length with additional 12" C length leads beyond armor.**

Insulated leadwires in flexible armor are available with either extruded PVC or Teflon® covering over the flexible armor. Substitute suffix codes T (Teflon®) or P (PVC) for the suffix "A" code above. **Example: T3T is Teflon® covered armor.**

Duplex elements supplied with individual leads.