


16A Bevel Seat^[1]



TUBE SIZE (inches)	O.D. (inches)	THICKNESS (inches)
1	1.31	0.46
1 1/2	1.84	0.56
2	2.37	0.62
2 1/2	2.90	0.66
3	3.43	0.71
4	4.50	0.81

[1] Must be manually cleaned

16AH H-Line



TUBE SIZE (inches)	O.D. (inches)	THICKNESS (inches)
1 1/2	2.00	0.250
2	2.50	0.250
2 1/2	3.03	0.250
3	3.56	0.250
4	4.68	0.250

16AI - 14I



TUBE SIZE (inches)	O.D. (inches)	THICKNESS (inches)
1 or 1 1/2	2.00	0.50
2	2.65	0.56
2 1/2	3.12	0.68
3	3.87	0.75
4	4.87	0.75

16AMP



TUBE SIZE (inches)	O.D. (inches)	THICKNESS (inches)
1/2 or 3/4	1.00	0.25
1 or 1 1/2	1.98	0.25
2	2.51	0.25
2 1/2	3.03	0.25
3	3.57	0.25
4	4.68	0.31

16APV



TUBE SIZE (inches)	O.D. (inches)	THICKNESS (inches)
1	1.38	0.29
1 1/2	1.88	0.42
2	2.38	0.46
2 1/2	2.88	0.47
3	3.38	0.50
4	4.38	0.53

16AQ - 14Q



TUBE SIZE (inches)	O.D. (inches)	THICKNESS (inches)
1 or 1 1/2	1.98	0.31
2	2.64	0.43
2 1/2	3.30	0.50
3	3.87	0.50
4	4.87	0.62