



Pyromation's high-temperature thermocouples are designed to operate in a temperature range of (982 to 1871) °C [1800 to 3400] °F. They are designed for use in vacuum furnaces and other applications requiring high-temperature measurement in controlled atmospheric conditions. Metal sheaths of Alloy 600 and molybdenum are available as well as alumina ceramic sheaths. All assemblies are supplied with ungrounded, isolated hot junctions. The construction style consists of an alumina-insulated element inside the tube of choice as listed below. Special construction designs are also available.

METAL-SHEATHED ASSEMBLY



ALUMINA-SHEATHED ASSEMBLY



ORDER CODES

Example Order Number:

1 2 3 4 5 6 7
R24U - **403** - **24** - **05A** - **TBL. 5** - **TBL. 6** - **TBL. 7**

Select from following page

1 Single Elements

TYPE AND WIRE GAUGE		CODE	SHEATH DIA. (inches)	MAX. TEMP.	ATMOSPHERE
CODE					
ALLOY 600		ALLOY 600			
B24U C24U R24U S24U	R26U S26U	303 303 303 303	0.188 0.188 0.188 0.188	1149 °C [2100 °F]	Oxidizing, Inert or Vacuum
B24U C24U R24U S24U	R26U S26U	403 403 403 403	0.250 0.250 0.250 0.250	1149 °C [2100 °F]	
MOLYBDENUM		MOLYBDENUM			
B24U C24U R24U S24U	R26U S26U	302 302 302 302	0.188 0.188 0.188 0.188	1704 °C [3100 °F] 1871 °C [3400 °F] 1482 °C [2700 °F] 1482 °C [2700 °F]	Inert or Vacuum
B24U C24U R24U S24U	R26U S26U	402 402 402 402	0.250 0.250 0.250 0.250	1704 °C [3100 °F] 1871 °C [3400 °F] 1482 °C [2700 °F] 1482 °C [2700 °F]	
ALUMINA		ALUMINA			
B24U C24U R24U S24U	R26U S26U	617 617 617 617	0.275 ^[1] 0.275 ^[1] 0.275 ^[1] 0.275 ^[1]	1704 °C [3100 °F] 1871 °C [3400 °F] 1482 °C [2700 °F] 1482 °C [2700 °F]	Oxidizing, Inert or Vacuum
For duplex elements use order code pre-fix letter twice. Example: RR24U		[1] Sheath supplied with 3/8" O.D. x 4" long stainless steel sleeve on tube cold end. Only available with size B and C compression fittings.			
CC24 assemblies not available in 0.188" O.D. sheath diameter.		Consult factory for availability of other diameters or insulations.			

[1] Sheath supplied with 3/8" O.D. x 4" long stainless steel sleeve on tube cold end.
Only available with size B and C compression fittings.

Consult factory for availability of other diameters or insulations.

4 Sheath Mounting Fittings

CODE	TYPE	NPT SIZE (inches)	AVAILABLE SHEATH DIA. (inches)
00	No sheath mounting fitting		
One-Time Adjustable Compression Fittings			
05A	Stainless steel	1/8	3/16, 1/4
05B	Stainless steel	1/4	3/16, 1/4, 3/8
05C	Stainless steel	1/2	1/4, 3/8
Re-Adjustable Compression Fittings			
12A	Stainless steel	1/8	3/16, 1/4
12B	Stainless steel	1/4	1/4, 3/8
12C	Stainless steel	1/2	1/4, 3/8
FEP gland standard (400 °F max.)			

3 Sheath "X" Length

LENGTH (inches)	LENGTH (inches)
12	30
18	36
24	
Specify other lengths in 1" increments.	

All assemblies are provided with wire seal fitting except platinum element assemblies in Alloy 600 tubes.
All C24 assemblies in alumina protection tubes can only be used in inert or vacuum atmospheres.