


Miniature thermocouple assemblies have very small swaged sheath diameters containing standard-purity MgO (96%) insulated thermocouple elements. The small sheath size provides accurate and fast response time temperature measurement in a variety of laboratory, process, and special applications. These units are only offered with ungrounded junctions to prolong their useful life. Illustrated below are the most commonly used assemblies, however, other sensor configurations are available upon request.



ORDER CODES

Example Order Number:

1-1 1-2 1-3 1-4 2 3 4 5
J 040 8 U - 012 - 00 - 16 - PAGE PAGE
MGO-7 MGO-7

1-1 Thermocouple Types

CODE

J

K

1-2 Sheath Diameter

CODE DIAMETER (INCHES)

032 0.032

040 0.040

1-3 Sheath Material

CODE MATERIAL

3 Alloy 600

8 316 Stainless steel

1-4 Measuring Junction

CODE MATERIAL

U Ungrounded junction

M Special limits
(consult factory)

2 "X" Dimension

Insert three digit sheath length
("X" Dimension) in inches

3 Sheath Terminations

CODE DESCRIPTION

4 Standard plug

5 Standard jack

6 Miniature plug

7 Miniature jack

Options

MC Mating connector

Leadwire Transitions

15 Extension leadwire transition fitting with relief spring
204 °C [400 °F]16 Extension leadwire transition fitting with heat-shrink
tubing 104 °C [220 °F]19 Extension leadwire transition ftg. w/o relief spring or
heat-shrink tubing 204 °C [400 °F]

Options

HT^[1] High Temperature Potting 538 °C [1000 °F]

[1] Not available with option 16. When specifying flex armor,
Option 19 must be selected.