

ORDER CODES

Unconfigured Order Number: T31-00^[1]

Example Configured Order Number:

T 3 1

-

1-0 2-0 3-0
3 85 U

-

4-0 5-0
S (50-300) F

1-0

CODE	DESCRIPTION
2	RTD (2-wire)
3	RTD (3-wire)
4	RTD (4-wire)

2-0

CODE	DESCRIPTION
85	100 ohm platinum ($\alpha = 0.003\ 85\ ^\circ\text{C}^{-1}$)
92	100 ohm platinum ($\alpha = 0.003\ 92\ ^\circ\text{C}^{-1}$)
95	1000 ohm platinum ($\alpha = 0.003\ 85\ ^\circ\text{C}^{-1}$)
[1] Default setting for unconfigured transmitter is 4-wire Pt100 (0 -100) °C.	

3-0

CODE	DESCRIPTION
U	Upscale Burnout $\geq 21.0\ \text{mA}$
D	Downscale Burnout $\leq 3.6\ \text{mA}$

4-0

RANGE
S (lower limit – upper limit)

5-0

CODE	DESCRIPTION
C	Celsius
F	Fahrenheit

Accessories

CODE	DESCRIPTION
10303	Communication Cable
10307	35 mm DIN-rail mounting clip